



Secure Kid™ Child Restraint

Owner's Manual

Keep for future use

Child Restraint System Exclusive RightFit Belt Path

Child Requirements

Harness Use

10 to 29.4 kg
(22 to 65 lbs)

71 to 127 cm
(28 to 50 in.)

Booster Use

18 to 49.8 kg
(40 to 110 lbs)

110 to 145 cm
(43.3 to 57 in.)

Para instrucciones en Español,
llamar al: 1-800-233-5921

WARNING:

To reduce the risk of serious injury
or death, read this owner's manual prior
to installing and using this child restraint.

More children are killed every year as passengers in car crashes than by any other type of injury.

To reduce the risk of **SERIOUS INJURY** or **DEATH**, read this owner's manual and your vehicle owner's manual before installing and using this child restraint. Using a child restraint makes a big difference. By properly using this child restraint and following these instructions (and the instructions that accompany your vehicle), you will greatly reduce the risk of serious injury or death to the child from a crash. Do not be misled by the commonly used term "safety seat"; no restraint system can prevent all injuries in all crashes. Many properly restrained adults and children are injured in motor vehicle crashes, including relatively minor crashes. A properly used child restraint is the best way to minimize injuries to the child and to increase the chances for the child's survival in most crashes.

U.S. REGULATORY NOTICE

This child restraint meets all applicable requirements of Federal Motor Vehicle Safety Standard 213.

**CANADIAN REGULATORY NOTICE
(Model numbers ending in "C.")**

This child restraint meets all applicable requirements of Canadian Motor Vehicle Safety Standards CMVSS 213 and 213.2.

- **No restraint can guarantee absolute protection from injury in every crash.**
- **This child restraint is designed for use by children in forward-facing and booster modes.**
*To use this child restraint properly, children **MUST** meet weight/size specifications as follows:*

For 5-pt Harness Use

- The child weighs 10 – 29.4 kg (22 – 65 lbs)
- The child is 71 – 127 cm (28 – 50 in.) **AND** the tops of their ears are at (or below) the child restraint headrest.
- Child is one year old or older.

For Booster Use

- The child weighs 18 – 49.8 kg (40 – 110 lbs)
- The child is 110 – 145 cm (43.3 – 57 in.) tall **AND** the tops of their ears are below the child restraint headrest.
- Child is four years old or older.

Important Information

Warnings 2
 Safe Practices 7
 Recall Information for U.S. Customers 8
 Public Notice for Canadian Customers 8
 Motor Vehicle / Aircraft Usage 8
 LATCH Information 9
 Care and Cleaning 9
 Visual Glossary 10

Using the Internal 5-pt Harness

Installation Checklist 13
 Installation with Lower Anchor Connectors 14
 Which Type of Lower Anchor Connector is on Your Child Restraint? 15
 Installation with Lower Anchor Hooks 15
 Installation with SureLatch Connectors 18
 Installation with Quick Connectors 22
 Installation with Vehicle Seat Belt 25
 Securing the Child 28
 Removing the Child 30
 Positioning the Harness Strap 31
 Positioning the Crotch Strap 33

Using a Booster Seat

When to Put Your Child in a Booster Seat 34
 Booster Installation Checklist 37
 Converting into a Booster Seat 38

General Information

Leveling the Booster Seat 42
 Booster Seat Belt Routing 42
 Using the SureLatch Connectors 43
 Using the Quick Connectors 43
 Using the Latch Hook Connectors 43
 Using the TruTether Adjuster 44
 Adjusting the Headrest 45
 Removing Seat Pad 45
 Removing Headrest Pad 45
 Securing Your Child Restraint in Aircraft 46
 Installing Child Restraint in Aircraft 47
 Replacement Parts 48
 Limited Warranty 50

Symbol Legend



Airbag Symbol – Alerts you to important information about airbag safety.



LATCH Symbol – Alerts you to important information about LATCH safety.



Tether Anchor Symbol – Alerts you to important information about tether anchor safety.

WARNING



Air Bag Warnings

- **DO NOT** use this restraint in the front seat of a vehicle equipped with an air bag. Air bags may cause serious injury or death to children 12 years of age and under. If your vehicle has an air bag, refer to your vehicle owner's manual for child restraint installation.
- If the rear seat of your vehicle is equipped with side air bags, refer to the following information for proper usage.

Vehicles built prior to the 2002 model year:


DO NOT use this restraint in a vehicle seating position equipped with a side air bag unless authorized by the vehicle manufacturer.

Model year 2002 and newer vehicles:

Refer to your vehicle owner's manual before placing this restraint in a seating position equipped with a side air bag.

- **DO NOT** place any objects between the restraint and the side air bag, as an expanding air bag may cause the items to strike the child.

The back seat is the safest place for children 12 and under.



WARNING

General Warnings

- Failure to follow installation instructions can result in the child striking the vehicle's interior during a sudden stop or crash. Serious injury or death may result. These instructions and the instructions in your vehicle owner's manual must be followed carefully. If there is a conflict between the two, the vehicle owner's manual regarding child restraint installation must be followed.
- **NEVER** leave child unattended.
- **DO NOT** use child restraint if it is damaged, broken, or missing parts.
- **DO NOT** use this restraint if it has been involved in a crash. It must be replaced.
- **NEVER** use this child restraint without the headrest installed.
- **NEVER** use this child restraint rear-facing.

Location Warnings

- **ALWAYS** read and follow exactly the instructions that accompany your vehicle and child restraint.
- According to statistics, children are safer when properly restrained in a rear seating position than in the front seating position. Generally, the center rear position is safest and should be used if available.
- Some child restraints do not fit all vehicles or all seating locations. There are many thousands of combinations of vehicle makes, models, child restraint configurations, seat belt designs, and seat cushion shapes. The easiest way to determine whether the child restraint is suitable for a particular seating position is to check for a tight installation. If the child restraint can not be properly installed, **DO NOT** use the child restraint. Consult vehicle owner's manual, try a different seating location or call Evenflo.
- **ONLY** use this child restraint on **forward-facing vehicle seats**. **DO NOT** use this restraint with vehicle seats that face the rear or side.
- **ONLY** use this child restraint on vehicle seats with backs that lock into place.

⚠️WARNING

Forward-facing Position Warnings

- If the child weighs more than 29.4 kg (65 lbs) or their shoulders are above the highest harness level, you **MUST** use this child restraint as a booster (p. 34).
- Adjust, or remove, the **vehicle** headrest, **in the seat where the child restraint is to be fastened**, so that the back of the child restraint rests against the vehicle seat back.
- The headrest on the vehicle seat in front of the child should be put in its lowest position. The vehicle seat back that the child faces must be fully padded and free of any hard objects.

Seat Belt Warnings

For 5-point Harness Use Only

- **DO NOT** use this child restraint if it moves more than 25 mm (1 inch) forward or side-to-side at the vehicle belt path. Serious injury or death may result from poor installation. If you can not tightly secure the child restraint, try again or move it to another location.

For Both 5-point Harness and Booster Use

- **DO NOT** use this child restraint in a vehicle with door-mounted seat belts.
- **DO NOT** use this child restraint in a vehicle with seat belts that automatically move along the vehicle frame when the door is opened. These seat belts will not hold a child restraint properly.
- **DO NOT** use this child restraint in a vehicle equipped with lap belts that only lock during a sudden stop or crash (emergency locking retractor – ELR). You must use a seating location with a locking seat belt. Check your vehicle owner's manual to see if you have lap belts with ELRs.
- If the vehicle seat belts are not routed and fastened correctly, the child restraint may not protect the child in a crash.
- **DO NOT** allow the seat belt release button to touch the child restraint. Accidental contact may cause the seat belt to release. If necessary, turn the seat belt release button away from the child restraint or move the child restraint to a different location.
- Failure to adjust the harness or vehicle seat belts snugly around the child may result in the child striking the vehicle's interior during a sudden stop or crash. Serious injury or death may occur.

⚠️WARNING

Seat Belt Warnings

For Booster Use Only

- When using this booster seat, **NEVER** use a lap belt only. You **MUST** use vehicle seat belts that have a lap/shoulder combination.
- The shoulder belt **MUST** be threaded through the shoulder belt guide (p. 36).
- **DO NOT** use this booster seat if the child's ears are above the back of the booster seat headrest.
- The shoulder belt **MUST NOT** cross the child's neck **or** fall off the child's shoulder. If you can not adjust the shoulder belt to **properly lay midway between the child's shoulder and neck AND at or above the shoulder**, try another seating location or do not use the booster seat.

LATCH Warnings

For 5-point Harness Use Only

- Do not use the lower anchors of the child restraint anchorage system (LATCH system) to attach this child restraint when restraining a child weighing more than 22.6 kg (50 lbs) with the internal harnesses of the child restraint.
- This LATCH system is intended to be used **ONLY** as described in these instructions. Serious injury or death may result from misuse.
- In addition to these instructions, read and follow your vehicle owner's manual regarding installation of the child restraint and LATCH. If there is a discrepancy, follow your vehicle owner's manual.
- **ONLY** use for securing child restraint to vehicle lower anchor bars.
- **NEVER** attach two lower anchor connectors to one vehicle lower anchor bar.
- **NEVER** use the vehicle seat belts when using the lower anchor connector assembly. Using both together can cause slack in a sudden stop or crash.
- When not in use, the lower anchor connector assembly should be securely stored on child restraint. Keep out of reach of children.

⚠️WARNING



LATCH Warnings – cont.

For 5-point Harness Use Only

- **ALWAYS** be sure that the lower anchor connectors are attached to the vehicle lower anchor bars by pulling hard on the lower anchor connectors. If they are not attached, the lower anchor connector assembly will not secure your child restraint. Serious injury or death may result.
- **DO NOT** use this child restraint if it moves more than 25 mm (1 inch) side to side or front to back at the belt path on the child restraint. Serious injury or death may result from poor installation. If you cannot tightly secure the child restraint, try again or move it to another location.



Tether Strap Warnings

- To avoid a strangulation hazard, you **MUST** tightly roll or fold excess or unused tether strap and secure with a rubber band. Attach the tether hooks to the storage clips when not in use (p. 11). This will keep an unused tether from hitting someone during a crash.

Additional Warnings

- In hot or sunny weather, **ALWAYS** check the areas of the child restraint that may contact your child (e.g., buckle, buckle tongues, etc.) for hot areas before placing him/her into the child restraint. The child could be burned. Cover the child restraint with a light colored blanket when you leave the vehicle.
- This child restraint must be securely fastened to the vehicle, **even when unoccupied**, using the vehicle seat belts or lower anchor connectors. An unsecured child restraint may injure someone if a crash occurs.
- **DO NOT** use the cup holders to store cans or hard cups. Only for use with soft cups (such as styrofoam or paper).
- **DO NOT** place any cups that contain hot liquids in the cup holders.
- **DO NOT** attach additional padding, toys, or other devices not made by Evenflo or described in these instructions for the child restraint. Items not tested with the child restraint could injure the child.

⚠️WARNING

Additional pads or pillows may interfere with the function of the harness system, or cause breathing problems if the child's head falls forward, increasing the risk of serious injury or death.

- Failure to follow installation instructions could result in serious injury or death. These instructions and the instructions in your vehicle owner's manual must be followed carefully. If there is a conflict between the two, the vehicle owner's manual regarding child restraint installation must be followed.
- In cold weather, **DO NOT** dress the child in bulky clothing like snowsuits if the child is riding in a child restraint. Bulky coats/snowsuits make it difficult to tighten the harness to the child, which may allow the child to be ejected from the restraint during a crash. If necessary, place a blanket over the harnessed child without interfering with the child restraint harness system.

Safe Practices

- **Everyone rides buckled up or the vehicle does not go.** Make no exceptions for adults or children. If someone unbuckles, stop the vehicle. Being firm and consistent from the start will mean fewer discipline problems as children get older. An unrestrained person can be thrown into and injure other passengers.
- **NEVER** try to tend to a crying baby's needs while driving. **NEVER** take a baby out of a child restraint for comforting while the vehicle is moving.
- **DO NOT** allow a child in a vehicle to have objects such as lollipops or ice cream on a stick. The object can injure the child if the vehicle swerves or hits a bump.
- **DO NOT** feed an infant who is riding in a child restraint.
- Put sharp or heavy items in the trunk. Anything loose can be deadly in a crash.

Recall Information for U.S. Customers

- Child restraints could be recalled for safety reasons. You must register this restraint to be reached in a recall. Send your name, address, the restraint's model number, and manufacturing date to **Evenflo Company, Inc., 1801 Commerce Dr., Piqua, OH 45356** or call 1-800-233-5921. You may also register on-line at:

www.evenflo.com/registercarseat

- For recall information, call the U.S. Government's Vehicle Safety Hotline at 1-888-327-4236 (TTY:1-800-424-9153), or go to:

www.NHTSA.gov

Public Notice for Canadian Customers

- To register your child restraint, return your registration card, call 1-937-773-3971, or register on-line at:

www.evenflo.com/registercarseatcanada

- For recall information, call Transport Canada at 1-800-333-0510 (1-613-993-9851 in Ottawa region) or Evenflo at 1-937-773-3971.

Motor Vehicle/Aircraft Usage

When used with the 5-point harness system and properly installed pursuant to these instructions,

this restraint is certified for use only in passenger and multi-purpose passenger motor vehicles, buses, and trucks equipped with Type I or II seat belts and in aircraft.



When used without the 5-point harness system (in booster mode) and properly installed pursuant to these instructions,


this restraint is certified for use only in passenger and multi-purpose passenger motor vehicles, buses, and trucks equipped with Type II seat belts. In booster mode, this restraint is **NOT** certified for aircraft use. A belt-positioning booster requires the use of a lap/shoulder belt system, which is not available on aircraft. Refer to pages 46 to 47 for instructions on installing your child restraint in aircraft.

LATCH Information

"**LATCH**" (Lower Anchors and Tethers for **C**hildren) is a system for attaching the child restraint to your vehicle seat. It can be used in place of the seat belts in vehicles with **LATCH** anchors. Refer to your vehicle owner's manual for the locations of **LATCH** anchors. **Note:** Your vehicle owner's manual may refer to this system as "**ISOFIX**" or "Universal Anchorage System (UAS)."

Care and Cleaning

- **DO NOT** lubricate or immerse the LATCH connectors, the buckle, or any part of this child restraint.
- Plastic and metal parts may be wiped clean with mild soap and water and dried with a soft cloth. Do not use abrasive cleaners or solvents.
- Take care not to damage any labels.
- The harness can be wiped clean with mild soap and water. Allow harness to air dry. **DO NOT** immerse buckle in water.
- Machine wash the seat pad separately in cold water, delicate cycle, and tumble dry 10 – 15 minutes on low heat.
- **NEVER** use child restraint without the seat pad.




For future reference, record the **model number** of your child restraint **AND** the **date of manufacture** below.

Model Number: _____


Date of Manufacture: _____

Visual Glossary

Your vehicle components may be significantly different than pictured. Consult your owner's manual to help you identify your vehicle components.





IMPORTANT: If your vehicle has **side air bags**, please refer to the warnings on page 2.



* Not available on all models.

Visual Glossary



* Not available on all models.

Using the Internal 5-pt Harness


Child Requirements

Weight: 10 – 29.4 kg (22 – 65 lbs)

Height: 71 – 127 cm (28 – 50 in.)


AND the tops of the child's ears are at, or below, the child restraint headrest.

Age: At least one year old



IMPORTANT

Evenflo strongly recommends using the top anchorage (tether) strap when using this seat with the internal harness. Using the tether strap will improve the stability of the child restraint and may reduce the risk of injury.



⚠ WARNING

If the child weighs more than 29.4 kg (65 lbs) or their shoulders are above the highest harness level, you **MUST** use this child restraint as a Booster.

Installation Checklist

1. Secure child restraint to the vehicle seat.

- ✓ Locking clip is installed, if necessary (p. 26).
- ✓ **If the child weighs 22.6 kg (50 lbs) or LESS**, the child restraint is securely installed with one of the following methods through the **upper belt path**:
 - *LATCH Hooks (p. 15)
 - *SureLatch Connectors (shown at left) (p. 18)
 - *Quick Connectors (p. 22)
 - Vehicle Seat Belt (p. 25)
- ✓ **If the child weighs MORE than 22.6 kg (50 lbs)**, the child restraint is securely installed with the **VEHICLE SEAT BELT ONLY** (not LATCH) through the **upper belt path** (p. 25).
- ✓ Tether strap is attached and tightened (p. 17, 21, 24, or 27).

2. Place the child in the child restraint.

- ✓ The child's back and bottom are flat against the back and bottom surfaces of the child restraint.
- ✓ The tops of the child's ears **MUST** be at, or below, the top of the child restraint headrest.

3. Make necessary adjustments.

- ✓ Crotch strap is properly positioned (p. 33).

4. Fasten both buckle tongues. Refer to page 28.

5. Tighten Harness - Position and connect chest clip.

- ✓ Harness straps are snug against the child's shoulders, with no slack (p. 29).
- ✓ Chest clip **MUST** be at armpit level (p. 29).


6. Check your work.

- ✓ To properly protect the child, the child restraint **MUST NOT** move more than 25 mm (1 inch) from **side-to-side** or from **front-to-back** at the upper belt path.

*To determine which LATCH connector is on your child restraint, go to page 15.

Installation with Lower Anchor Connectors

LATCH is a system for attaching the child restraint to your vehicle seat. It is to be used in place of your vehicle's seat belts and can be used in vehicles with LATCH anchors. Your vehicle owner's manual may refer to this system as ISOFIX, Universal Anchorage System (UAS), or Lower Universal Anchorage System.



DO NOT install by this method for a child weighing more than 22.6 kg (50 lb).

WARNING

- **ONLY** use for securing child restraint to lower anchor bars.
- **ALWAYS** read and follow exactly the instructions which accompany your vehicle and child restraint.
- **NEVER** attach two hooks to one vehicle lower anchor bar.
- **DO NOT** use the vehicle seat belts to install a child restraint when using the Lower Anchor Connector Assembly.
- This Lower Anchor Connector Assembly is intended to be used **ONLY** as described in these instructions. Serious injury or death may result from misuse.
- **ALWAYS** be sure that the Lower Anchor Connector hook is fully engaged onto the Vehicle Lower Anchor Bar by pulling hard on the Lower Anchor Connector strap. If it is not totally engaged, the Lower Anchor Connector Assembly will not secure your child restraint. Serious injury or death may result.
- To avoid a strangulation hazard, you **MUST** store the unused lower anchor connector assembly, with all slack removed, in storage area on the back of the seat. Roll or fold excess lower anchor connector strap and secure with a rubber band to prevent serious injury to vehicle occupants.
- In addition to these instructions, read and follow your vehicle owner's manual regarding installation of child restraints and LATCH. If there is a discrepancy, follow your vehicle owner's manual.

Which Type of Lower Anchor Connector is on Your Child Restraint?


In order to properly install your child restraint with the LATCH system, you must first know which type of LATCH connectors are present on your child restraint.

- If your child restraint has **LATCH Hook Connectors**, begin installation by referring to "Installation with LATCH Hook Connectors," below.
- If your child restraint has **SureLatch Connectors**, begin installation by referring to page 18, "Installation with SureLatch Connectors."
- If your child restraint has the **Quick Connectors**, begin installation by referring to page 22, "Installation with Quick Connectors."


Lower Anchor Hooks



SureLatch™ Connector




Quick Connector™




Installation with Lower Anchor Hooks

IMPORTANT:

- Some vehicle manufacturers have lower maximum weight ratings for LATCH anchors. Consult your vehicle owner's manual, or call the vehicle manufacturer, to confirm the limits on your vehicle's LATCH anchors.
- If you are using the vehicle seat belt to secure the child restraint, **DO NOT** use the Lower Anchor Hooks.
- Install this child restraint with the vehicle seat belt (**NOT** Lower Anchor Hooks) if the child weighs more than 22.6 kg (50 lbs).




1. **Disconnect Tether Hook and Lower Anchor Hooks from the back of the child restraint.**



2. Place the child restraint in position.


Set child restraint on vehicle seat in forward-facing position, as shown. Lay the tether strap over the back of the vehicle seat.



3. Attach Lower Anchor Hooks.

Attach a LATCH Hook Connector onto **each** seat anchor.


IMPORTANT: Make sure both LATCH connectors are facing upward and the harness straps are not twisted.



4. Secure the child restraint.

Using your full weight, push the child restraint firmly into the vehicle seat while pulling up on the LATCH strap to tighten.

IMPORTANT: To properly protect the child, the child restraint **MUST NOT** move more than 25 mm (1 inch) from side-to-side or from front-to-back **at the upper belt path**. If you cannot tightly secure the child restraint, try again or move it to another location.



5. Connect and tighten tether strap.


Connect the tether hook to the anchor behind the vehicle seat, as shown. Pull the strap and tighten the tether securely.

IMPORTANT: If your tether strap is too short to reach from your child restraint to your vehicle tether anchor, you will need a Tether Extender. Please call ParentLink at 1-800-233-5921 (U.S.) or 1-937-773-3971 (Canada), or 01-800-706-12-00 (Mexico).

Notice

Your child restraint is equipped with one of two types of tether adjusters: standard (shown above) or the TruTether (shown below). If your child restraint is equipped with the TruTether adjuster, refer to page 44 for information about proper tightening.


TruTether Adjuster



Installation with SureLatch Connectors


IMPORTANT:

- Some vehicle manufacturers have lower maximum weight ratings for LATCH anchors. Consult your vehicle owner's manual, or call the vehicle manufacturer, to confirm the limits on your vehicle's LATCH anchors.
- If you are using the vehicle seat belt to secure the child restraint, **DO NOT** use the SureLatch Connectors.
- Install this child restraint with the vehicle seat belt (**NOT** SureLatch connectors) if the child weighs more than 22.6 kg (50 lbs).



1. Disconnect Tether Hook from the back of the child restraint.


Tether Strap



2. Place the child restraint in position.

Set child restraint on vehicle seat, as shown. Lay the Tether Strap over the back of the vehicle seat.

Installation with SureLatch Connectors





3. Attach SureLatch Connectors.

With the SureLatch harness through the upper belt path, as shown above, push each SureLatch connector onto each seat anchor.

Note: You may need to vary the angle of the SureLatch connectors, as shown above, to attach to the anchor.

IMPORTANT: Position the SureLatch connectors so they are facing upward, sitting above the LATCH guide, as shown, and the straps are not twisted.







4. Secure the child restraint.

Using your full weight, push the child restraint firmly into the vehicle seat, as shown, to set it in place.

IMPORTANT: To properly secure this child restraint, it **MUST NOT** move more than 25 mm (1 inch) from side-to-side or from front-to-back **at the upper belt path**. If you can not tightly secure the child restraint, try again, move it to another location, or install with vehicle seat belt.



Make sure that each SureLatch connector is above the LATCH guide, as shown.



5. Connect and tighten Tether Strap.


Connect the Tether Hook to the anchor behind the vehicle seat, as shown. (Please consult your vehicle owner's manual, as tether anchor locations may vary.) Pull the strap and tighten the Tether securely.

IMPORTANT: If your tether strap is too short to reach from your child restraint to your vehicle tether anchor, you will need a Tether Extender. Please call ParentLink at 1-800-233-5921 (U.S.) or 1-937-773-3971 (Canada), or 01-800-706-12-00 (Mexico).

Notice


Your child restraint is equipped with one of two types of tether adjusters: standard (shown above) or the TruTether (shown below). If your child restraint is equipped with the TruTether adjuster, refer to page 44 for information about proper tightening.

TruTether Adjuster




IMPORTANT:

- Some vehicle manufacturers have lower maximum weight ratings for LATCH anchors. Consult your vehicle owner's manual, or call the vehicle manufacturer, to confirm the limits on your vehicle's LATCH anchors.
- If you are using the vehicle seat belt to secure the child restraint, **DO NOT** use the Quick Connectors.
- Install this child restraint with the vehicle seat belt (**NOT** Quick connectors) if the child weighs **more than 22.6 kg (50 lbs)**.




1. Disconnect Tether Hook from the back of the child restraint.



2. Place the child restraint in position.

Set child restraint on vehicle seat, as shown. Lay the Tether Strap over the back of the vehicle seat.




3. Attach Quick Connectors.

With the Quick Connector harness through the upper belt path, as shown above, push a Quick Connector onto the Lower Anchor Bar on each side of the child restraint.


Note: You may need to vary the angle of the Quick Connectors, as shown above, to attach to the anchor.

IMPORTANT: Make sure both LATCH Quick Connectors are facing upward, above the LATCH guide, as shown, and the straps are not twisted.

Correct




Incorrect



4. Secure the child restraint.

Using your full weight, push the child restraint firmly into the vehicle seat while pulling up on the Quick Connector Strap to tighten.

IMPORTANT: To properly secure this child restraint, it **MUST NOT** move more than 25 mm (1 inch) from side-to-side or from front-to-back **at the upper belt path**. If you can not tightly secure the child restraint, try again, move it to another location, or install with vehicle seat belt.



5. Connect and tighten Tether Strap.


Connect the Tether Hook to the anchor behind the vehicle seat, as shown. (Please consult your vehicle owner's manual, as tether anchor locations may vary.) Pull the strap and tighten the Tether securely.

IMPORTANT: If your tether strap is too short to reach from your child restraint to your vehicle tether anchor, you will need a Tether Extender. Please call ParentLink at 1-800-233-5921 (U.S.) or 1-937-773-3971 (Canada), or 01-800-706-12-00 (Mexico).

Notice


Your child restraint is equipped with one of two types of tether adjuster: standard (shown above) or the TruTether (shown below). If your child restraint is equipped with the TruTether adjuster, refer to page 44 for information about proper tightening.

TruTether Adjuster




IMPORTANT:

- Before installing this child restraint with the vehicle seat belt, you **MUST** make sure the Lower Anchor Hooks, SureLatch or Quick Connectors are attached to the storage D-rings on the seat pad.
- When using the vehicle seat belt to secure the child restraint, **DO NOT** use the Lower Anchors. Using both together can cause slack in a sudden stop of crash.
- Check your vehicle owner's manual to determine how to lock your seat belt for child restraint installation. The seat belt must be locked to properly secure the child restraint.




1. Disconnect Tether Hook from the back of the child restraint.




2. Place the child restraint in position.

Set child restraint on vehicle seat, as shown. Lay the Tether Strap over the back of the vehicle seat.



3. Route seat belt through upper belt path.

Route the seat belt buckle tongue through the upper belt path, as shown.



4. Buckle seat belt.

Installation with Vehicle Seat Belt



5. Remove all slack from the seat belt.

Using your full weight, push the child restraint firmly into the vehicle seat while tightening the seat belt to remove excess slack.

6. Install Locking Clip (not included), if necessary.

If your vehicle was built prior to model year 1996, and has a lap/shoulder belt that is equipped with an emergency locking retractor (ELR) AND sliding latch plate, you **MUST** use a Locking Clip. Check your vehicle owner's manual to identify which vehicle belt system is in your vehicle.

If your vehicle is **model year 1996 or newer**, it likely has a vehicle belt system that can be locked when tightened, and will not require use of a Locking Clip.

Consult your vehicle owner's manual before installing a locking clip.

If your vehicle requires a Locking Clip, please call ParentLink at 1-800-233-5921 (U.S.) or 1-937-773-3971 (Canada), or 01-800-706-12-00 (Mexico) to obtain a Locking Clip and instructions on how to install and use it. to obtain a Locking Clip and instructions on how to install and use it.

⚠ WARNING

- Remove Locking Clip from vehicle seat belt when not used with a child restraint, or the vehicle seat belt will not properly restrain an adult or child. Serious injury could occur.
- **DO NOT** use a Locking Clip in booster mode.


Installation with Vehicle Seat Belt



7. Ensure child restraint is secure.


Hold the child restraint near the upper belt path, as shown, and try to move it in all directions.

IMPORTANT: To properly secure this child restraint, it **MUST NOT** move more than 25 mm (1 inch) from side-to-side or from front-to-back **at the upper belt path**. If you can not tightly secure the child restraint, try again or move it to another location.



8. Connect and tighten Tether Strap.

Connect the Tether Hook to the anchor behind the vehicle seat, as shown. (Please consult your vehicle owner's manual, as tether anchor locations may vary.) Pull the strap and tighten the Tether securely.




IMPORTANT: If your tether strap is too short to reach from your child restraint to your vehicle tether anchor, you will need a Tether Extender. Please call ParentLink at 1-800-233-5921 (U.S.) or 1-937-773-3971 (Canada), or 01-800-706-12-00 (Mexico).

Notice

Your child restraint is equipped with one of two types of tether adjusters: standard (shown above) or the TruTether adjuster (shown below). If your child restraint is equipped with the TruTether adjuster, refer to page 44 for information about proper tightening.

TruTether Adjuster



Securing the Child



1. Loosen harness.


Press the harness release button on the front of the seat while pulling the harness straps.



2. Position harness straps.

Unfasten chest clip and place the child in the child restraint. Bring each harness strap over the child's shoulders.

IMPORTANT: The child's back and bottom should be flat against the restraint. If there is a gap, the child will not be comfortable.



3. Buckle the harness.

Insert both buckle tongues into the buckle.

Note: Pull up on the harness straps to ensure that the buckle tongues are fastened securely.

Securing the Child



4. Fasten and adjust chest clip.

Snap the two halves of the chest clip together, as shown, and slide to armpit level.



5. Tighten harness.

Pull the harness adjuster strap to tighten the harness.

Note: Check the harness straps near the shoulders for slack. You should **NOT** be able to pinch the harness (see illustration). Adjust as needed.

IMPORTANT: A snug strap should not allow any slack. It lies in a relatively straight line without sagging. It does not press on the child's flesh or push the child's body into an unnatural position.

Removing the Child




1. Loosen harness straps.

Press the harness release button on the front of the seat while pulling the harness strap outward behind the fastened chest clip.



2. Disconnect chest clip.

Push the release button and pull the chest clip apart.



3. Unbuckle harness.

Press the red button on the buckle and release both buckle tongues.


You may now remove the child.

Positioning the Harness Strap



1. Loosen harness straps.

Press the harness release button on the front of the seat while pulling the harness straps.



2. Remove both harness straps from the splitter plate.

Positioning the Harness Strap




3. Move harness strap.

Remove both harness straps from the slots and feed them into the new slot, as shown. Pull the harness strap to the back of the child restraint.

Note: Straps must be positioned at the child's shoulder level or slightly above.


IMPORTANT: When inserting harness straps through the slots in the seat pad, make sure you route them correctly through their corresponding slots in the seat shell.



4. Attach harness straps to splitter plate.

Attach the loop at the end of each harness strap onto the splitter plate.


IMPORTANT: Make sure both harness straps are installed completely on the splitter plate, as shown.



Positioning the Crotch Strap


As your child grows, you will need to change the crotch strap position so that it is in the slot closest to your child. The crotch strap should **ALWAYS** be as close as possible to, but **NEVER** under, the child's bottom.

IMPORTANT: You **MUST** place the crotch strap in the front slot if your child weighs 18 kg (40 lbs) or more.



1. Remove crotch strap.

Loosen the harness straps and move them out of the way. Push the anchor up through the slot to the top of the seat.



2. Insert crotch strap into new slot.

Insert the crotch strap anchor into the slot that is the closest to the child **AND** the most comfortable for the child.

Pull the crotch strap to make sure it is secure.

When to Put Your Child in a Booster Seat

Booster seats raise the child up and help to position the vehicle lap and shoulder belt correctly. When the child is **properly restrained** in a booster seat, their risk of injury in all types of crashes is reduced, as the lap and shoulder belt provides excellent restraint of both the upper and lower torso.

It is important for the child to sit properly within the vehicle seat belts. When the vehicle seat belt is buckled, the lap belt should be low on the hips, just touching the thighs, and the shoulder belt should lie across the middle of the shoulder. If the child leans out or moves the belt behind the back or places it under the arm, **it will not provide the intended restraint.**

There are a number of things to consider when deciding whether the child is ready to sit in a booster seat, including: the weight and height rating on their current child seat, the child's own weight and height, their maturity, and the seating positions available in your vehicle.

How is a booster seat used?


Using a booster seat is very similar to buckling yourself into the vehicle:

- Read the instruction manuals for both the booster seat and the vehicle before you start.
- Put the booster in the back seat in a location with a lap and shoulder belt. **Never use a booster with only a lap belt**, as this could cause serious injuries.
- After the child is in the booster, pull the lap and shoulder belt across him/her and buckle it.
- Check that the shoulder belt lies across the middle of the shoulder and that the lap belt is low on the hips, just touching the thighs.

How can you tell if your child is ready to transition to a booster seat?

You should consider using a booster seat if the following conditions apply:

- The child is mature enough to sit in the booster seat and not put the belts under their arm or behind their back.
- The child is approaching the weight or height limit of the child restraint they are currently using.
- If you have a vehicle that does not have a tether anchorage but has lap/shoulder belts available in the back seat, a booster seat may provide better protection than an internal harness seat without the tether.



Using as a Booster Seat


Child Requirements

Weight: 18 – 49.8 kg (40 – 110 lbs)

Height: 110 – 145 cm (43.3 – 57 in.)

tall **AND** the tops of the child's ears are at, or below, the child restraint headrest.

Age: At least four years old



The shoulder belt **MUST** pass through shoulder belt guide and **under** the headrest.

The shoulder belt **MUST** cross midway between child's shoulder and neck.

The lap belt is stretched low and snug across the child's hips and routed under the lap belt guides.

This line **MUST** be level to the ground (Canadian Models Only).



IMPORTANT

Always secure the booster seat with the LATCH connectors or vehicle seat belt when not occupied.

An unsecured booster seat can fly into and injure other occupants in the event of a crash.

Booster Installation Checklist


- 1. Convert child restraint to booster seat.**
See "Converting into a Booster Seat," p. 38.
- 2. Secure booster seat to the vehicle seat.**
 - ✓ Make sure the bottom and back of the booster seat are touching vehicle seat and back.
 - ✓ Level the booster seat (Canadian models only), p. 42.
- 3. Place the child in the booster seat.**
Make sure the child's back and bottom are flat against the back and bottom surfaces of the booster seat.
- 4. Adjust headrest for proper shoulder belt fit.**
The top of the child's ears are at, or below, the child restraint headrest and the shoulder belt **MUST** cross midway between the child's shoulder and neck, as shown at left.
- 5. Secure child and booster seat to vehicle seat.**
 - ✓ Stretch the lap/shoulder belt across the child and fasten the buckle. Make certain the shoulder belt is threaded through the shoulder belt guide on the headrest.
 - ✓ Confirm belt routing p. 42.
- 6. Check your work.**

⚠ WARNING


- The shoulder belt **MUST NOT** cross the child's neck or fall off the child's shoulder. If you can not adjust the shoulder belt to properly lay midway between the child's shoulder and neck **AND** at or above the shoulder, try another seating location, or do not use the booster seat.



Converting into a Booster Seat



- 1. Loosen harness.**
Press the harness release button while pulling outward on the harness straps, as shown. Disconnect the chest clip.



- 2. Remove both harness straps from the splitter plate and pull them through to the front of the seat.**




- 3. Disconnect all J-clips and all retaining strips, then remove the seat pad.**


Converting into a Booster Seat




- 4. Route the harness straps through adjustment slots, then attach to splitter plate.**




IMPORTANT: Make sure both harness straps are installed completely on the splitter plate.



- 5. Tuck the chest clip and buckle tongues into the recesses on either side of the seat shell.**






Converting into a Booster Seat




6. Remove the crotch strap.

Locate the crotch strap anchor on the bottom. Turn the anchor sideways and push it through the seat shell to remove, as shown.



Insert the crotch strap anchor back into the opening from the bottom of the child restraint.



Pull the anchor through the seat and adjust so it lies flat, as shown.

Converting into a Booster Seat



7. Install the seat pad.


Your child restraint is now in Booster Mode and ready for a child who weighs 18 – 49.8 kg (40 – 110 lbs), is 110 – 145 cm (43.3 – 57 in.) tall, is at least four years old, and whose ears are below the top of the child restraint headrest.

Note: to convert the seat back into 5-point harness mode, reverse these steps.

General Information

Leveling the Booster Seat

Canadian Models Only



If the level line is not parallel to the ground, before fastening child to the vehicle seat, place a tightly rolled towel/ small blanket beneath the bottom rear of the booster seat, as shown.

Booster Seat Belt Routing


Canadian models:

Only the lap belt must pass under the guide & fasten into the buckle.


US models:

When used with a child that weighs 18 - 29.4 kg (40 - 65 lbs) both the lap belt and the shoulder belt must pass under the guide & fasten into the buckle.

When used with a child that weighs 29.4 - 49.6 kg (65 - 110 lbs) only the lap belt must pass under the guide & fasten into the buckle.



Using the SureLatch Connectors




To remove the SureLatch Connector from a LATCH anchor or a storage D-ring, press the red Release Button.

Using the Quick Connectors



To remove the Quick Connector from a LATCH anchor or a storage D-ring, pull the red Release Strap.

Using the Latch Hook Connectors





To remove the Latch Hook Connector from a LATCH anchor or a storage D-ring, press the tab and twist, then remove the hook.

Using the TruTether Adjuster

Not available on all models.


Tether straps equipped with the TruTether adjuster attach to vehicle tether anchor brackets exactly the same as Tether Straps with standard tether adjusters. TruTether adjusters, however, are equipped with a Tightness Indicator that shows, at a glance, whether the Tether Strap is properly tightened. When the Tightness Indicator Display is "green," the Tether Strap is tight enough.

TruTether Adjuster



Connect the Tether Hook to the anchor behind the vehicle seat, as shown. Pull the strap until you see green in the tightness indicator display. Once it has turned green, you have removed all slack and the Tether Strap is adequately tightened. Be sure to check it periodically to make sure the indicator is still green. If no green is showing, pull the strap until it is.


Adjusting the Headrest



To adjust, press the lock release button, as shown, while sliding the headrest up or down to the desired position.

IMPORTANT: When the headrest is in one of the four locking positions, the locking button will pop into its original position.

Removing Seat Pad



1. Disconnect the harness straps from the splitter plate.
2. Disconnect all J-clips and all retaining strips. Remove the seat pad.

Removing Headrest Pad



Disconnect all J-clips and remove the headrest pad.

Securing Your Child Restraint in Aircraft

The Federal Aviation Administration (FAA) recommends that you secure your child for air travel in an appropriate child restraint based on your child's weight and size. Turbulence can happen with little or no warning. When turbulence occurs, **the safest place for your child is in a properly installed child restraint, not in an adult's lap or on the aircraft seat with its seat belt.** Keeping your child in a child restraint during the flight will help ensure your family arrives safely at your destination.

The FAA recommends that a child weighing:

- more than 18 kg (40 lbs) use an aircraft seat belt;
- less than 9 kg (20 lbs) use a rear-facing child restraint; and
- from 9 to 18 kg (20 to 40 lbs) use a forward-facing child restraint.


Please note that these FAA recommendations may vary from those applicable to the use of your child restraint in a motor vehicle.

IMPORTANT

You must use the internal harness when installing the child restraint in aircraft.

Installing Child Restraint in Aircraft


IMPORTANT: Before installing the child restraint, make sure the **aircraft seat is in a fully upright position.**



1. Place the child restraint in position.

Place the child restraint on the aircraft seat forward-facing, as shown above.


Installing Child Restraint in Aircraft



2. Route aircraft seat belt through belt path.

Route the aircraft seat belt through the belt path opening in the back of the child restraint and continue through the opening on the opposite side of the child restraint.

Note: Lift the restraint's seat pad away for easier access.



3. Fasten the aircraft seat belt, then remove all slack from the belt.

The aircraft seat belt must be as tight as possible. Route the excess aircraft seat belt strap back through the belt path opening. Using your full weight, push the child restraint firmly onto the aircraft seat while pulling on the excess seat belt strap to tighten.


Note: Because of the fixed length of aircraft seat belts, the belt buckle could be behind the child's back after tightening the belt. For your child's comfort, Evenflo recommends cushioning the child's back by placing a small pillow or folded-up blanket, or a folded-up jacket, over the belt buckle.

Check your work: Reconnect the seat pad to the front of the child restraint. Try to move the child restraint in all directions. If you can move the restraint more than 25 mm (1 inch) from side-to-side or front to back **at the belt path**, the aircraft seat belt is not tight enough, and you **MUST** install again until the seat belt is tight.

Replacement Parts

Not available on all models.


You can order replacement parts on-line at www.evenflo.com or contact Evenflo. When you contact us, please have the product model number and date of manufacture (found on the back of the child restraint).




Locking Clip:
(Not included with
child restraint),
see page 26.



Cup Holder/Armrest




Headrest
Pad



Tether Extender
(Not included with
child restraint)




Chest Clip



Harness System




Seat Pad



LATCH Harness with
Hook Connectors




Head Foam



LATCH Harness with
SureLatch Connectors

Or



LATCH Harness with
Quick Connectors


Proper Disposal of This Child Restraint

At the end of this child restraint's useful life, Evenflo encourages you to dispose of it properly. Most of the components in this child restraint are recyclable.

1. Remove all fabric and padding.
 2. Remove all screws and disassemble the restraint.
 3. Recycle all plastic/foam parts and discard the rest.
- If your local recycling center won't accept the padding, you may dispose of it in the landfill.

Note: Evenflo uses recycled materials in the manufacturing process whenever possible but never for components that are critical for safety.

To prevent injury due to hidden damage, lost instructions, outdated technology, etc., discontinue use of this restraint after the expiration date on the label or if it has been involved in a crash.



After thoroughly reading and following these instructions, store them in the slots on either side of the child restraint.

Manufactured in / Fabriqué en
(year-month-day) / (année-mois-jour)
Name / Nom
Model / Modèle
Made in / Fabriqué en
Expires on / Expire le

Limited Warranty

For a period of 90 days from the original purchase of this Product, Evenflo warrants to the original end user (“Purchaser”) this Product (including any accessories) against defects in material or workmanship. Evenflo’s sole obligation under this express limited warranty shall be, at Evenflo’s option, to repair or replace any Product that is determined to be defective by Evenflo and determined to be covered by this warranty.

Repair or replacement as provided under this warranty is the exclusive remedy of the Purchaser. Proof of purchase in the form of a receipted invoice or bill of sale evidencing that the Product is within the warranty period must be presented to obtain warranty service. This express limited warranty is extended by Evenflo ONLY to the original Purchaser of the Product and is not assignable or transferable to subsequent purchasers or end users of the Product. For warranty service, contact Evenflo’s ParentLink Consumer Resource Center at **www.evenflo.com**.


EXCEPT TO THE EXTENT PROHIBITED BY APPLICABLE LAW, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ON THIS PRODUCT IS HEREBY DISCLAIMED. EVENFLO SHALL NOT BE LIABLE FOR ANY INCIDENTAL, CONSEQUENTIAL, SPECIAL OR PUNITIVE DAMAGES OF ANY KIND FOR BREACH OF THE EXPRESS LIMITED WARRANTY ON THIS PRODUCT, OR ANY WARRANTY IMPLIED BY OPERATION OF LAW. OTHER THAN THE EXPRESS LIMITED WARRANTY SET FORTH ABOVE, THERE ARE NO OTHER WARRANTIES THAT ACCOMPANY THIS PRODUCT AND ANY ORAL, WRITTEN OR ANY OTHER EXPRESS REPRESENTATION OF ANY KIND IS HEREBY DISCLAIMED.

ParentLink®

answers. advice. affirmation.™

• **www.evenflo.com**

- **USA:** 1-800-233-5921, 8 AM to 5 PM E.T.
- **Canada:** 1-937-773-3971
- **México:** 01-800-706-12-00



INSTRUCTIONS

ParentLink®

answers. advice. affirmation.™

www.evenflo.com

USA: 1-800-233-5921, 8 AM to 5 PM E.T.

Canada: 1-937-773-3971

México: 01-800-706-12-00